



Innovative Tile and Stone  
Installation Systems

# 5 Year System Warranty

APPLICATION	PRODUCTS
Underlayment	LATICRETE® 84 Latilevel LATICRETE Admix & Primer
Vapor Reduction	LATAPOXY® 312 Vapor Reduction Membrane
Waterproofing	LATICRETE Hydro Ban™ LATICRETE Hydro Barrier™ LATICRETE 9235 Waterproofing Membrane LATAPOXY Flashing Mortar * LATICRETE 302 Waterproofing * LATICRETE 9237 Waterproofing Membrane
Sound Control	LATICRETE 170 Sound & Crack Isolation Mat
Anti-Fracture	LATICRETE Blue 92 Anti-Fracture Membrane
Thick Bed Method	LATICRETE 3701 Mortar Admix mixed with LATICRETE 226 Thick Bed Mortar LATICRETE 3701 Fortified Mortar Bed * LATICRETE 3642 Latex mixed with LATICRETE 226 Thick Bed Mortar
Slurry Bond Coat	LATICRETE 254 Platinum * LATICRETE 73 Crete Admix mixed with LATICRETE 211 Powder * LATICRETE 335 Super Flex
Thin Bed Method	LATICRETE 253 Gold (regular or rapid version) LATICRETE Sure Set™ LATICRETE 333 Super Flexible Additive mixed with LATICRETE 317 (exterior use limited to residential/light commercial applications; do not use in areas subject to water immersion) * LATICRETE 335 Super Flex * LATICRETE 73 Crete Admix mixed with either of the following <ul style="list-style-type: none"> <li>▪ LATICRETE 211 Powder; or</li> <li>▪ LATICRETE 317; or</li> <li>▪ LATICRETE 290</li> </ul>
Grouting	LATICRETE 1776 Grout Enhancer mixed with either of the following <ul style="list-style-type: none"> <li>▪ LATICRETE 1500 Sanded Grout; or</li> <li>▪ LATICRETE 1600 Unsanded Grout; or</li> <li>▪ * LATICRETE 500 Sanded Grout; or</li> <li>▪ * LATICRETE 600 Unsanded Grout</li> </ul>
Sealant†	LATICRETE Latasil™ LATICRETE Latasil 9118 Primer

† Use of suitable flexible sealant is required per Tile Council of North America Detail EJ171 for use in expansion joints, coves, corners, changes in plane and other joints or wherever tile or stone abuts dissimilar materials or restraining surfaces.

\* Available in markets outside of the United States of America and Canada

## LIMITED WARRANTY

Subject to the conditions and limitations stated below, LATICRETE INTERNATIONAL, INC. ("LATICRETE") warrants that the products listed on this document will be free from manufacturing defects and will not break down or deteriorate under normal usage for a period of five (5) years from the date of purchase when installed in accordance with the written specifications of LATICRETE and industry standard guidelines. For this limited warranty to apply, the applications that comprise the installation must be performed with the products listed in this document for each application (refer to chart).

## DISCLAIMER

THIS LIMITED WARRANTY IS GIVEN IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED. THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES BASED ON SAMPLES OR ORAL STATEMENTS, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE OF THIS DOCUMENT. IMPLIED WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED.

## EXCLUSIVE REMEDY

The sole and exclusive remedy for a breach of this limited warranty is replacement of only the specific portion of the installation that is proven to be defective\*\*. LATICRETE will pay for replacement of its own products and replacement of finishing materials, as well as for labor for the replacement installation, but LATICRETE will not pay more, calculated on a square-foot (square-meter) basis, for the replacement than the original purchase price of the portion being replaced. LATICRETE will not pay for replacement of any portion of the installation that is not proven to be defective.

In the event that the sole and exclusive remedy described above fails of its essential purpose, the liability of LATICRETE is limited to the monetary value, on a square-foot (square-meter) basis, of the original purchase price of the portion being replaced.

Notwithstanding the previous paragraphs, exterior facades with ceramic tile or stone installed over substrates with steel or wood framing **do not qualify** for this limited warranty—see Data Sheet 230.15 and 230.15MVIS for such applications.

\*\*NOTE: Efflorescence is a normal condition of portland cement mortars and is not a defective condition.

## EXCLUSIONS

LATICRETE is not responsible for workmanship not in accordance with the instructions of LATICRETE and industry standard guidelines. Cracking due to structural movement, excessive deflection or other failure in the substrate is also not covered.

LATICRETE IS NOT LIABLE FOR ANY INCIDENTAL DAMAGES OR CONSEQUENTIAL DAMAGES, INCLUDING LOSSES DUE TO DELAYS, INCURRED BY THE PURCHASER OR ANY OTHER PARTY.

## NO ASSIGNMENT

This limited warranty is not transferable or assignable.

## HOW TO MAKE A CLAIM

To make a claim under this limited warranty, you must notify LATICRETE in writing within thirty (30) days of the discovery of the alleged manufacturing defect. At the option of LATICRETE, you may be required, as a condition of this limited warranty, to provide proof of product purchase and use.

## Address your claim to:

LATICRETE International, Inc.  
1 LATICRETE Park North  
Bethany, CT 06524-3423 USA  
Attn.: Technical Services Department

## TECHNICAL INFORMATION

Technical assistance and information is available by calling the LATICRETE Technical Services Line:

Toll Free: 1.800.243.4788, ext. 235  
Telephone: +1.203.393.0010, ext. 235  
Fax: +1.203.393.1948

LATICRETE International, Inc.  
One LATICRETE Park North  
Bethany, CT 06524-3423 USA  
1.800.243.4788  
+1.203.393.0010  
www.laticrete.com

©2010 LATICRETE International, Inc.  
LATICRETE, LATAPOXY, SPECTRALOCK and the  logo are Registered Trademarks of LATICRETE International, Inc.

DS-230.05-0310