



Admix & Primer

DS-662.0-0310



1. PRODUCT NAME

LATICRETE® Admix & Primer

2. MANUFACTURER

LATICRETE International, Inc.
1 LATICRETE Park North
Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 235
Toll Free: 1.800.243.4788, ext. 235
Fax: +1.203.393.1684
Internet: www.laticrete.com

3. PRODUCT DESCRIPTION

LATICRETE Admix & Primer is a latex primer for use with LATICRETE 86 LatiLevel™ and LATICRETE 84 LatiLevel . It is also used as an admix for LATICRETE 816 LatiPatch™. Product is for interior use only.

Uses

A re-emulsifiable bonding agent designed to be used with LATICRETE Latasil Self Leveling Underlayments and LATICRETE 816 LatiPatch.

Advantages

- Easy to use
- Reduces pinholes
- Allows for proper hydration of self leveling underlayment
- Increases bond strength

Suitable Substrates

For interior uses only

- Concrete
- Cement Backer Board*
- Cement Terrazzo**
- Exterior Glue Plywood
- Ceramic Tile and Stone**
- Cement Mortar Beds

* Consult cement backer board manufacturer for specific installation recommendations and to verify acceptability for exterior use.

** Skim coat existing flooring with LATICRETE® 254 Platinum

Packaging

5 quarts (4.8 l) jug, 4 jugs per carton, 28 cartons per pallet

Approximate Coverage

- For extremely porous dry substrates, may be applied full strength, yielding approximately 250 ft² (23.2 m²) per jug or dilute 1:1 by volume with clean potable water to yield approximately 500 ft² (46.4 m²) per jug.
- When used as an admix with LATICRETE 816 LatiPatch, coverage will depend upon the thickness desired. Refer to Data Sheet for LATICRETE 816 LatiPatch for further details on approximate coverage (see 10. FILING SYSTEM).

Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for five (5) years if stored at temperatures >32°F (0°C) and <110°F (43°C).

Limitations

- Interior Use Only
- Do not install when surface temperature is below 40°F (4°C) or when ambient temperature is expected to be below 50°F (10°C) during placement or before material takes final set.
- Adhesives/mastics, mortars and grouts for ceramic tile, pavers, brick and stone are not replacements for waterproofing membranes. When a waterproofing membrane is required, use a LATICRETE Waterproofing Membrane (see Section 10 FILING SYSTEM).

Cautions

Consult MSDS for more information

- During cold weather, protect finished work from traffic until fully cured.
- Keep out of reach of children.

4. TECHNICAL DATA

Applicable Standard

Meets all Federal, State & Local requirements for VOC.

Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

Surface Preparation

All surfaces should be between 40°F (4°C) and 90°F (32°C) structurally sound, clean and free of all dirt, oil, grease, loose peeling paint, concrete sealers or curing compounds. Remove all dust by vacuuming. Skim coat existing ceramic tile or stone with a LATICRETE Latex Thin-Set Mortar.

Application

- Instructions for use as a primer for self-leveling applications: Use LATICRETE Admix and Primer with every application. Shake thoroughly before using. Pour, mop, or spray primer onto the surface. Apply an even thickness to the prepared substrate using a bristle broom. Make sure to work into the substrate, removing any puddles or thick areas. Allow the primer to dry to

a clear film (usually 2–3 hours but less than 24 hours) before application of underlayment. Very dry or porous slabs will require double priming if diluted with water.

- Instructions for use as an admix: Mix 5 quarts (4.8 l) with 1 bag of LATICRETE® 816 LatiPatch™ to a creamy smooth consistency; apply product as needed.

Cleaning

Clean tools with water while primer is fresh.

6. AVAILABILITY AND COST

Availability

LATICRETE and LATAPOXY® materials are available worldwide.

For distributor information:

Toll Free: 1.800.243.4788
Telephone: +1.203.393.0010
Internet: www.laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM

DS 230.13: LATICRETE Product Warranty

A component of:

DS 230.05: LATICRETE 5 Year System Warranty
DS 025.0: LATICRETE 25 Year System Warranty
DS 230.99: LATICRETE Lifetime System Warranty

8. MAINTENANCE

LATICRETE and LATAPOXY grouts require routine cleaning with a neutral pH soap and water. All other LATICRETE and LATAPOXY materials require no maintenance but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

9. TECHNICAL SERVICES

Technical assistance

Information is available by calling:

Toll Free: 1.800.243.4788, ext. 235
Telephone: +1.203.393.0010, ext. 235
Fax: +1.203.393.1948

Technical and safety literature

To acquire technical and safety literature, please visit our website at www.laticrete.com.

10. FILING SYSTEM

Additional product information is available on our website at www.laticrete.com. The following is a list of related documents:

DS 230.13: LATICRETE Product Warranty
DS 230.05: LATICRETE 5 Year System Warranty
DS 025.0: LATICRETE 25 Year System Warranty
DS 230.99: LATICRETE Lifetime System Warranty
DS 236.0: LATICRETE 9235 Waterproofing Membrane
DS 674.0: LATICRETE 816 LatiPatch
DS 084.0: LATICRETE 84 LatiLevel™
DS 238.5: LATICRETE 86 LatiLevel
DS 677.0: LATICRETE 254 Platinum
DS 663.0: LATICRETE Hydro Ban™

LATICRETE International, Inc.
One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

©2010 LATICRETE International, Inc.
LATICRETE, LATAPOXY, SPECTRALOCK and the  logo are Registered Trademarks of LATICRETE International, Inc.

DS-662.0-0310