



MATERIAL SAFETY DATA SHEET

Form

F 7.3.29Rev: **B**
Page: **1 of 6**
Date: **01/25/07**

MATERIAL SAFETY DATA SHEET

I. PRODUCT IDENTIFICATION

TRADE NAME (as labeled): **LATICRETE® SpectraLOCK™ Pro Part B**

CHEMICAL FAMILY: Epoxy Resin

MANUFACTURER'S NAME: LATICRETE INTERNATIONAL, INC.
1 Laticrete Park, N.
Bethany, CT 06524-3423 USA

Phone number for additional information: (203) 393-0010

Date prepared or revised: 12/2011 Name of preparer: S.B. Fine

II. HAZARDOUS INGREDIENTS

CHEMICAL NAMES	CAS NUMBERS	PERCENT	ACGIH TLV	OSHA PEL	OTHER (SPECIFY)
Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	25085-99-8	45-52	N/A	N/A	N/A
Reaction product: Bisphenol F-(epichlorhydrin); epoxy	28064-14-4	10-17	N/A	N/A	N/A
Alkyl(C12-14) glycidyl ether	68609-97-2	7-14	N/A	N/A	N/A
Xylenes	1330-20-7	0.1-0.2	100 ppm	100 ppm	N/A

N/A = Not applicable or available

	Form	F 7.3.29
	MATERIAL SAFETY DATA SHEET	
		Rev: B Page: 2 of 6 Date: 01/25/07

----- III. HEALTH HAZARD INFORMATION -----

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure.

Inhaled: May cause irritation of respiratory tract.

Contact with skin or eyes: May cause eye irritation. Corneal injury is unlikely. Vapor may cause eye irritation experienced as mild discomfort and redness. A component in this mixture has caused allergic skin reactions in humans. Contains component(s) which have caused allergic skin sensitization in guinea pigs.

Absorbed through skin: N/A

Swallowed: N/A

SUSPECTED CANCER AGENT?

 x NO: This product's ingredients are not found in the lists below.

YES: Federal OSHA NTP IARC

-----IV. FIRST AID: EMERGENCY PROCEDURES-----

Eye Contact: Hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin Contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

Inhaled: Move patient to fresh air. If breathing has stopped or is labored give assisted respiration (e.g. mouth-to-mouth). Supplemental oxygen may be indicated. Prevent aspiration of vomit. Turn victim's head to the side. Seek medical advice.

Swallowed: If swallowed, call a physician immediately. Do not induce vomiting. Never give anything by mouth to an unconscious person.

----- V. FIRE AND EXPLOSION -----

Flash Point method): Non-flammable

Auto ignition temperature, °F: N/A

Flammable limits in air, volume %: N/A Lower (LEL) Upper (UEL)

Fire extinguishing materials:

 water spray

 x foam

 x carbon dioxide

 x dry chemical

 other:



MATERIAL SAFETY DATA SHEET

Form

F 7.3.29

Rev: **B**
Page: **3 of 6**
Date: **01/25/07**

Special fire fighting procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize properly damage. Water fog, applied gently may be used as a blanket for fire extinguishment. Contain fire water run-off if possible, Firewater run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this MSDS. Wear positive pressure self-contained breathing apparatus.

Unusual fire and explosion hazards: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Phenolics. Carbon monoxide. Carbon dioxide.

----- VI. SPILL, LEAK, AND DISPOSAL PROCEDURES -----

Spill response procedures (include employee protection measures): respirators, safety glasses, and long sleeved clothing; avoid the generation of dust. Contain spilled material if possible. Absorb with materials such as: Sand. Polyethylene fiber products. Polypropylene fiber products. Collect in suitable and properly labeled containers. Remove residual with soap and hot water. Residual can be removed with solvent. Solvents are not recommended for clean-up unless the recommended exposure guidelines and safe handling practices for the specific solvent are followed.

Preparing wastes for disposal (container types, neutralization, etc) N/A

NOTE: Dispose of all wastes in accordance with federal, state and local regulations.

-----VII. Handling and Storage-----

Store in cool areas. Excess heating over long periods of time degrades the resin

----- VIII. Exposure Controls and Personal Protection -----

Ventilation and engineering controls: Normal

Respiratory protection (type): NIOSH approved respirators if exposure limits are exceeded.

Eye protection (type): Safety glasses or goggles

Gloves (specify material): Impervious gloves

Other clothing and equipment: Long sleeved clothing

	Form	F 7.3.29
	MATERIAL SAFETY DATA SHEET	

Rev: **B**
Page: **4 of 6**
Date: **01/25/07**

Work practices, hygienic practices: Normal Good housekeeping

Other handling and storage requirements: N/A

Protective measures during maintenance of contaminated equipment: See above.

----- IX. PHYSICAL PROPERTIES -----

Vapor density (air=1): N/A	Melting point or range, °F: >32
Specific gravity: 1.12 g/cc	Boiling point or range, °F: >212
Solubility in water: soluble	Evaporation rate (butyl acetate = 1): N/A
Vapor pressure, mmHg at 20°C: N/A	
Appearance and odor: opaque liquid.	

HOW TO DETECT THIS SUBSTANCE (warning properties of substance as a gas, vapor, dust, or mist): N/A

----- X. REACTIVITY DATA -----

Stability: X Stable Unstable

Conditions to avoid: Stable at ambient temperatures. Excess heating over long periods of time degrades the resin.

Incompatibility (materials to avoid): Contact with acids, oxidizing materials, bases, accidental contact with amines

Hazardous decomposition products (including combustion products): (from burning, heating, or reaction with other materials).

Incomplete pyrolysis or combustion results in phenolics, carbon monoxide, carbon dioxide, and water. Thermal decomposition should be traced as a potentially hazardous substance.

Hazardous polymerization: May occur X Will not occur

Conditions to avoid: N/A

----- XI. Toxicology Information -----

Acute Dermal Toxicity (LD50, Rabbit) >2,000 mg/kg

Single dose oral LD50, Rat > 2,000 mg/kg



MATERIAL SAFETY DATA SHEET

Form

F 7.3.29

Rev: B
Page: 5 of 6
Date: 01/25/07

XII. Ecological Information

Movement & Partitioning

Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5). Potential for mobility in soil is low (Koc between 500 and 2000). Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

ECOTOXICITY

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested). Toxicity to aquatic species occurs at concentrations above material's water solubility.

Fish Acute & Prolonged Toxicity

LC50, fathead minnow (*Pimephales promelas*), static, 96 h: 3.1 mg/l

Aquatic Invertebrate Acute Toxicity

EC50, water flea *Daphnia magna*, static, 48 h, immobilization: 1.4 - 1.7 mg/l

NOEC, water flea *Daphnia magna*, static renewal, 21 d, survival: 0.3 mg/l

Aquatic Plant Toxicity

ErC50, *Scenedesmus capricornutum* (fresh water algae), static, Growth rate inhibition, 72 h: >11 mg/l

Toxicity to Micro-organisms

IC50: bacteria. 18 h: > 42.6 mg/l

XIII. Disposal Information

Dispose in compliance with local, state, and federal regulations.

XIV. Transport Information

Proper Shipping Name: Environmentally Hazardous Substance Liquid, n.o.s. - Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers and Bisphenol F-(epichlorhydrin); epoxy resin) 9 UN3082 PG III

EMS Number: F-A,S-F

Marine pollutant.: Yes

For DOT non-bulk, the MARINE POLLUTANT and Class 9 label is not required on a combination packaging for liquids, inner packagings not over 5.0 L (1.3 gallons) net capacity each packed in strong outer packaging. However package may not exceed 30 kg (66 lbs) per package. If so the Marine Pollutant and Class 9 Label must be applied along with the Proper Shipping Name and UN number.

For IMDG non-bulk, the MARINE POLLUTANT and Class 9 label is not required on a combination packaging for liquids, inner packagings not over 5.0 L (1.3 gallons) net capacity each packed in strong outer packaging, and the limited quantity Diamond Label must be applied to the package. The package may not exceed 30 kg (66 lbs) per package. If so the Marine Pollutant and Class 9 Label must be applied along with the Proper Shipping Name but no Limited Quantity Diamond Label and UN number.

ICAO/IATA REGULATED Do not ship by air



Form

F 7.3.29

MATERIAL SAFETY DATA SHEET

Rev: **B**
Page: **6 of 6**
Date: **01/25/07**

-----XV. Regulatory Information-----

All ingredients are listed on the U.S. EPA TSCA inventory of chemical substances.
Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning
and Community Right-to-Know Act of 1986) Sections 311 and 312
Immediate (Acute) Health Hazard Yes
Delayed (Chronic) Health Hazard No
Fire hazard No
Reactive Hazard No
Sudden Release of Pressure Hazard No

This product contains a chemical known to the State of California to cause cancer or reproductive harm.

HMIS Ratings Health – 1 Flammability – 0 Reactivity – 0 Personal Protection - B

-----XVI Other Information-----

This information is furnished without warranty, representation, inducement or license of any kind; except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be accurate.